

VFVX321


VCXO Ultra Low Jitter 2.5V, 3.3V

5x7mm SMD, LVPECL / LVDS / LVCMOS



Features

- 60MHz to 800MHz* frequency range
- Differential output levels (LVPECL/LVDS)
- Single ended LVCMOS output available
- <0.2ps RMS jitter over 12kHz to 20MHz
- Selectable OE logic



Applications

- Optical Networking, SONET / SDH
- 10 Gigabit Ethernet
- Broadband Access

Electrical Specifications

Parameter	Symbol	Condition	Min	Typ	Max	Unit	Note
Frequency Range	F		60 60 60		800* 320 250	MHz	PECL LVDS CMOS
Frequency Stability	$\Delta F/F$	Vs. Operating temperature			± 50 ± 25 ± 20	ppm	Order Code B Order Code C Order Code D
		Vs. Supply voltage		± 3		ppm/V	
		Vs. Aging / Year		± 3 ± 1		ppm ppm	First Year After first year
Operating Temperature	T		0° -40°		+70° +85°	°C	Order Code B Order Code G
Output		LVPECL LVDS LVCMOS					Order Code L Order Code D Order Code C
Supply Voltage	V_{CC}		3.15 2.25	3.3 2.5	3.45 2.75	V	Order Code E Order Code G
Period RMS Jitter		155.52MHz 311.04MHz 622.08MHz		2.5 2.8 4	3 3.3 6	ps	
Integrated RMS Jitter 12kHz to 20MHz		155.52MHz 311.04MHz 622.08MHz		0.25 0.18 0.09		ps	

* NOTE: Certain frequencies above 300MHz ($2.5V_{DD}$) are not available.
Consult factory for availability.

VFVX321
VCXO Ultra Low Jitter 2.5V, 3.3V
5x7mm SMD, LVPECL / LVDS / LVCMOS



Electrical Specifications

Parameter	Symbol	Condition	Min	Typ	Max	Unit	Note
Supply Current	I_{CC}	38 – 100MHz			65	mA	PECL
		100 – 300MHz			80		
		300 – 640MHz			90		
		38 – 100MHz			45	mA	LVDS
		100 – 320MHz			60		
		At 100MHz, load = 15pF		16	20	mA	CMOS
Load		50 Ohms to $V_{DD}-2V$ (PECL) 100 Ohms (LVDS)					
Output High Voltage	V_{OH}	$R_L = 50$ Ohms to $(V_{DD}-2V)$ $I_{OH} = -8.5mA$	2.4	$V_{DD}-1.025$ 1.4	1.6	V	PECL LVDS CMOS
Output Low Voltage	V_{OL}	$I_{OL} = -8.5mA$	0.9	1.1	$V_{DD}-1.620$ 0.4	V	PECL LVDS CMOS
Output Differential Voltage	V_{OD}		247	355	454	mV	LVDS
Output Drive Current	I_{OSD}	$V_{OL} = 0.4V,$ $V_{OH} = 2.4V$		8.5		mA	CMOS
Offset Voltage	V_{OS}		1.125	1.2	1.375	V	LVDS
Rise / Fall Time	T_R/T_F	20% to 80%		0.25 0.5 1.2	0.45 0.7 1.6	ns	PECL LVDS CMOS
Duty Cycle		$V_{DD} - 1.3V$ @ 1.25V 50% V_{DD}	45	50	55	%	PECL LVDS CMOS
Modulation Bandwidth		$0V < V_C < 3.3V;$ -3dB	16			kHz	
V_C Input Impedance			130			k Ω	
Linearity				5	10	%	
APR*	V_{DD}	3.3V $V_C 1.65V$ $\pm 1.65V$	± 100 ± 75 ± 50	± 120 ± 100 ± 75	ppm		60 – 150MHz 151 – 399MHz 400 – 800MHz
		2.5V $V_C 1.25V$ $\pm 1.25V$	± 100 ± 75 ± 50	± 120 ± 90 ± 65			60 – 130MHz 131 – 200MHz 200 – 400MHz
Stabilization Time		From valid power			10	ms	
Tristate	“1”: Output Enable – Pin 2 may float or 2.8V min (3.3V V_{DD}) or 2.25V min (2.5V V_{DD}) “0”: Tristate – Pin 2 requires 0.4V max (3.3V or 2.5V V_{DD})						

*Consult factory for wider pull availability

VFVX321
VCXO Ultra Low Jitter 2.5V, 3.3V
5x7mm SMD, LVPECL / LVDS / LVCMOS



Phase Noise Performance

Parameter	Output Type	Frequency Range (MHz)	Carrier Freq. (MHz)	10Hz	100Hz	1kHz	10 kHz	100 kHz	1 MHz	10 MHz
Phase Noise (dBc/Hz)	PECL	400 - 800	622.08	-49	-85	-110	-130	-137	-148	-150
	CMOS	120 - 250	155.52	-50	-82	-110	-128	-142	-148	-150
	PECL LVDS	120 - 320	155.52	-50	-82	-110	-128	-142	-148	-150
	CMOS	60 - 160	155.52	-65	-95	-122	-138	-142	-148	-149
	PECL LVDS	60 - 160	155.52	-65	-95	-122	-138	-142	-148	-149

Absolute Maximum Ratings

Parameter	Symbol	Condition	Min	Typ	Max	Unit	Note
Lead Temperature		Soldering, 10s max			260	°C	
Storage Temperature	T _s		-55		+125°	°C	
Junction Temperature	T _J				+125°	°C	
ESD Protection		Input static discharge voltage protection			2	kV	
Supply Voltage	V _{DD}				4.6	V	
Output Voltage	V _O		GND -0.5		V _{DD} +0.5	V	
Input Voltage			GND -0.5		V _{DD} +0.5	V	

Environmental and Mechanical Conditions

Parameter	Condition
Shock	1000 Gs, 0.35ms, ½ sine wave, 3 shocks in each plane
Humidity	Resistant to 85% R.H. at 85 °C
Vibration	10-2000 Hz of 0.06" d.a. or 20 Gs, whichever is less
Leak	MIL STD 883, Method 1014, Condition A and Condition C
Case	Ceramic with hermetic resistance-welded metal lid
Pads	Solderable gold over nickel
Marking	Epoxy ink or laser engraved
Resistance to Solvents	MIL STD 202, Method 215

VFVX321

VCXO Ultra Low Jitter 2.5V, 3.3V

5x7mm SMD, LVPECL / LVDS / LVCMOS



Pin Assignments

LVPECL, LVDS


Pin #	Connection
1	V _C
2	Tristate
3	Case, GND
4	Output
5	Output
6	Supply Voltage

LVCMOS


Pin #	Connection
1	V _C
2	Tristate
3	Case, GND
4	Output
5*	N/C
6	Supply Voltage

*For LVCMOS, Dual single ended outputs available – consult factory


Package



Marking Specification



How to Order



Note: DG combination not available at all frequencies. Consult factory.