
SMD Crystal Unit

FCX-04C









FEATURES

- AT-cut crystal unit / frequency range 8 ~ 60 MHz.
- 3.2 × 2.5 × 0.7 mm Max. / 18 mg.

060

(3)

- Frequency tolerance ±7 ppm available.
- Automotive operating temperature range -40 ~ +125°C available.
- · Ceramic with metal lid sealed by patented Electron-Beam-Soldering.
- Supports frequencies as low as the those of 5032 size.

+ APPLICATIONS

 Applications that require pulling-sensitivity equal to or higher than that of 5032 size.

◆ STANDARD SPECIFICATIONS / ORDERING INFORMATION

8.000 ~ 60.000 MHz

Ordering Number (Sample):

В

С

D

E

(1) (2)
(2) Nominal Frequency

(4) (5) (6) (7) (8) (9)

(3) Load Capacitance

5.0, 6.0, 7.0 pF*1 e.g. 6.0 pF = 060

*1 Other capacitances available

(1) Type	
C4C	
	_
(4) Frequency Tolerance)
@ 25°C	

±7 ppm ±10 ppm

±15 ppm

±20 ppm

±30 ppm

±50 ppm Other

(5) Operating Temperature	Frequency Temperature Characteristics (with reference to 25°C)					
	±10 ppm	±15 ppm	±20 ppm	±30 ppm	±50 ppm	
-20 ~ +70°C	P1	P2	P3	P4	P5	
-30 ~ +85°C	Q1	Q2	Q3	Q4	Q5	
-40 ~ +85°C	-	R2	R3	R4	R5	
-40 ~ +105°C	-	-	-	S4	S5	
-40 ~ +125°C	-	-	-	-	T5	
Other			NN			

10000

e.g. 10.000 MHz = 10000

(6) Equivalent Series Resistance				
8 ~ 9.5 MHz: 300Ω Max.	300			
9.5 ~ 12 MHz: 150Ω Max.	150			
12 ~ 13 MHz: 80Ω Max.	080			
13 ~ 16 MHz: 60Ω Max.	060			
16 ~ 60 MHz: 50Ω Max.	050			
Other	NNN			

(7) Storage Temperature*2		
-40 ~ +85°C	G	
-40 ~ +105°C	Н	
-55 ~ +125°C	J	
Other	N	
*2 Not applicable to packing materials		


(8) Tape & Reel (φ180 mm)		
3000 pcs/reel	X	
Other	N	


(9) RIVER Use Only (As needed)


Drive Level 200 µW Max.

- The codes for the Ordering Number are indicated in blue, and the specifications are described in black.
- Not all combinations of options are available as standard.
- AEC-Q200 complaint spec available upon request.
- For specifications that include "Overall Frequency-Tolerance", please select "N" for the (4) Frequency Tolerance and let us know your specific requirements.
- For specifications other than those above, please contact our sales / website and let us know your specific requirements.


OUTLINE DEMENSIONS












◆ LAND PATTERN

Unit: mm



SIVER