

## CO2016 SERIES: 2.0 x 1.6 mm CLOCK OSCILLATOR

### ■ FEATURES

- ULTRA MINATURE PACKAGE
- ESSENTIAL IN HIGH DENSITY PCB
- LOW SUPPLY VOLTAGE 1.8 AND 2.5 VDC AVAILABLE
- STANDBY FUNCTION

### ■ APPLICATIONS

- PRINTER SCANNER
- VGA CARD
- DVD
- DSC, DVC



### ■ ELECTRICAL SPECIFICATION

PARAMETER		VALUE		
Frequency Range		1.5 ~ 50.000 MHz		
Operating Temperature Range		-10°C to +70°C		
Frequency Stability <sup>1</sup> **		±25 ppm, ±30 ppm, ±50 ppm, ±100 ppm		
Storage Temperature Range		-40°C to +85°C		
Supply Voltage (Vcc)		1.8V ±5%	2.5V ±5%	3.3V ±5%
Supply Current		2.5 mA max ~24 MHz 3.5 mA max ~40 MHz 4.5 mA max ~50MHz	3.0 mA max ~24 MHz 4.5 mA max ~40 MHz 5.0 mA max ~50 MHz	2.5 mA max ~24 MHz 3.5 mA max ~40 MHz 4.5 mA max ~50 MHz
Output CMOS	Symmetry	45% to 55% at 50% Vdd		
	Rise / Fall Time	10 nsec max at 10% to 90% Vdd		
	Logic "0" Level	Vcc x 0.1 V max		
	Logic "1" Level	Vcc x 0.9 V min		
	Load	15 pF max		
Enable / Disable Function		Pin 1: High or Open >> Output enabled Pin 3 Pin 1: Low >> Output disabled (High impedance)		

\*\* Inclusive of 25°C tolerance, operating temperature range, voltage or load changes, aging, shock and vibration, consult factory for tighter stability options.


### NOTES

<sup>1</sup> Not available at all frequencies, Contact Factory

<sup>2</sup> Check part numbering table below. For others contact factory.

### CO2016 SERIES: 2.0 x 1.6 mm CLOCK OSCILLATOR

#### MECHANICAL SPECIFICATION (4 pin ceramic package)



#### PART NUMBERING SYSTEM

TYPE	SERIES	-	FREQUENCY (MHz)	-	SUPPLY VOLTAGE (Vcc)	-	STABILITY (PPM)	-	TAPE & REEL
Clock Oscillator	2016	-	1.5 ~ 50.000	-	1.8: Vcc=1.8 2.5: Vcc=2.5 3.3: Vcc=3.3	-	25: ±25 ppm 30: ±30 ppm 50: ±50 ppm 100: ±100 ppm	-	TR
CO	2016	-	12.800	-	2.5	-	50	-	TR

#### EXAMPLE: CO2016-12.800-2.5-50-TR

Surface Mount CO2016, 2.0 x 1.6 mm, 12.800 MHz, 2.5 VDC Supply Voltage, ±50 ppm Overall Stability, from -10°C to +70°C, Symmetry 45% to 55%, Tape and Reel packaging.