

SMD ONE PORT 303.825 MHz SAW RESONATOR

ASR303.825E



5 x 5 x 1.5mm

STANDARD SPECIFICATIONS:

CHARACTERISTICS		UNIT	MIN.	TYP.	MAX.
Center Frequency Fo		MHz	303.75	303.825	303.9
Tolerance from Fo		KHz		±75	
Insertion Loss		dB	-	1.3	2.5
Quality Factor	Unloaded	-		12,000	
	50Ω loaded			2,000	
Temperature Stability	Turnover Temperature	°C		39.0	
	Turnover Frequency	KHz		Fo	
	Freq. Temp. Coefficient	ppm/°C ²		0.032	
Frequency Aging		ppm/year		<±10	
DC Insulation Resistance		MΩ	1.0		
RF Equivalent RLC Model	Motional Resistance R ₁	Ω		12	19
	Motional Inductance L ₁	μH		94.0	
	Motional Capacitance C ₁	fF		2.9	
	Shunt Capacitance C ₀	pF	2.7	3.0	3.3
Operating temp.		°C	-40°C to +85°C		
Storage temp.		°C	-45°C to +85°C		
Max. Rating	DC voltage	V	±10		
RF Power Dissipation		dBm	0		


Data measured with: Source Impedance: Z_s=50Ω, Load Impedance: Z_L=50Ω, T_A=25°C
Electrostatic Sensitive Device. Handle with precaution.

MARKING:


- 303.82 (303.825 Frequency in MHz)
- AR ZYX (ZY: Date code Z for month from A to L; Y for year, i.e. 4 for 2004
X: Traceability code)

PIN NO.	CONNECTIONS
1	Input GND
2	Input
5	Output GND
6	Output
3,7	To be GNDed
4,8	Case GND

OUTLINE DRAWING:



FREQUENCY RESPONSE:



TEST CIRCUIT:

